



(43) International Publication Date
3 February 2005 (03.02.2005)

PCT

(10) International Publication Number
WO 2005/010407 A1


- (51) International Patent Classification⁷: **F16H 61/04**
- (21) International Application Number:
PCT/JP2004/010169 ✓
- (22) International Filing Date: 9 July 2004 (09.07.2004) ✓
- (25) Filing Language: English ✓
- (26) Publication Language: English ✓
- (30) Priority Data:
2003-202710 ✓ 28 July 2003 (28.07.2003) ✓ JP ✓
- (71) Applicants (for all designated States except US): **TOYOTA JIDOSHA KABUSHIKI KAISHA** [JP/JP]; 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP); **AISIN AW CO., LTD.** [JP/JP]; 10, Takane, Fujii-cho, Anjo-shi, Aichi 4441192 (JP). ✓
- (72) Inventors; and
- (75) Inventors/Applicants (for US only): **KONDO, Masami** ✓

[JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP); **MATSUBARA, Tooru** [JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP); **TANAKA, Yoshikazu** [JP/JP]; c/o TOYOTA JIDOSHA KABUSHIKI KAISHA, 1, Toyota-cho, Toyota-shi, Aichi 4718571 (JP); **SATO, Yasushi** [JP/JP]; c/o AISIN AW CO., LTD., 10, Takane, Fujii-cho, Anjo-shi, Aichi 4441192 (JP); **YOSHIDA, Satoshi** [JP/JP]; c/o AISIN AW CO., LTD., 10, Takane, Fujii-cho, Anjo-shi, Aichi 4441192 (JP); **FUKATSU, Akira** [JP/JP]; c/o AISIN AW CO., LTD., 10, Takane, Fujii-cho, Anjo-shi, Aichi 4441192 (JP); **WATANABE, Kiyoshi** [JP/JP]; c/o AISIN AW CO., LTD., 10, Takane, Fujii-cho, Anjo-shi, Aichi 4441192 (JP). ✓

(74) Agents: **FUKAMI, Hisao** et al.; Fukami Patent Office, Mitsui Sumitomo Bank, Minamimorimachi Bldg., 1-29, Minamimorimachi 2-chome, Kita-ku, Osaka-shi, Osaka 5300054 (JP).

[Continued on next page]

(54) Title: **SHIFT CONTROL DEVICE OF AUTOMATIC TRANSMISSION**



(57) Abstract: A shift control device of an automatic transmission (300) comprising detection means for detecting a shift from a non-drive to a drive position; output means for outputting a command to execute an engine (100) output lowering; detection means (410) for detecting a transmission input revolution number and control means (1020) for engaging the friction (engagement (310)) element by direct pressure control in response to a detection of said transmission input revolution number having been decreased to a predetermined value.



(81) **Designated States** (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

(84) **Designated States** (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.